

CORDAFLEX® NSHTÖU-J (SMK)-V 0.6/1kV



Rubber reeling cable



Application: Extra heavy duty rubber reeling cable for control and power supplies. For applications with high mechanical stresses, especially for simultaneous tensile and torsion stresses. Suitable for motor-driven reels, spring-operated reels, drum-spreader, festoon- and hoisting systems.

Construction and technical data:

Standard:	DIN VDE 0250 -814 (with ref. to)
Conductor material:	bare copper strand
Conductor construction:	class „FS“ = exceptionally fine stranded
Insulation:	polyolefin
Material inner sheath:	rubber compound based on PCP
Self-supporting element:	aramide
Torsion protection:	synthetic braid
Torsion:	+/- 50 °/m
Sheathing material:	rubber compound based on PCP
Colour of outer sheath:	yellow
UV-resistant:	yes
Oil-resistant:	EN 60811-404
Max. temperature at conductor, °C:	90 °C
Permitted outer cable temperature, fixed, °C:	-50 - +80 °C
Permitted outer cable temperature, moved, °C:	-35 - +80 °C
Bending radius, fixed installation:	4 x Ø
Bending radius, moving application:	6 x Ø
operating speed spreader, m/min.:	240 m/min.
Nominal voltage U₀/U :	0.6 / 1 kV
Test voltage:	3.5 kV



part no.	part name	RI [Ohm/km]	I _{bl} [A]	Ø [mm]	F _{zd} [N]	Cu	G [kg]
051853	24X2.5	7.98	30	29.2	2700	672	1344
051444	30X2.5	7.98	30	32.4	4100	840	1680
051789	44X2.5	7.98	30	37.1	5100	1232	2194
052186	49X1	19.5	18	29.6	3700	546	1288
052014	56X2.5	7.98	30	43.1	6000	1567	3065
053056	20x2,5+3xCAN-BUS +2x(2x2,5)C	7.98	30	45.9		895	2791

RI	Conductor resistance
I _{bl}	Ampacity in air (30 °C)
Ø	outer diameter approx.
F _{zd}	Tensile strength (dynamic)
Cu	Copper weight (GER)
G	net weight per 1000

The products and information presented here are for technical calculation only. They are subject to technical progress and in no way represent the ability of shipment. Outer diameters are approximately.



CABLES INDUSTRIELS DE CHAMPAGNE - Z.A.M. Les Crayères - F-51520 LA VEUVE
Tél. +33 (0)326 684 822 - Fax. +33 (0)326 685 964 - www.cic-cables.com



Données/valeurs théoriques non contractuelles

Non-contractual theoretical datas/values