

**CABLES MARINES**  
SANS HALOGENE  
NON PROPAGATEUR DE L'INCENDIE

# CIC-SHIP SH-PC-X

**SHIPBOARD CABLES**  
HALOGEN FREE  
FIRE RETARDANT



**CABLES DE PUISSANCE & CONTRÔLE**  
IEC 61892-4 / IEC 60092-353

Température maxi au conducteur : 90°C

**0,6/1 kV**

**POWER & CONTROL CABLES**  
IEC 61892-4 / IEC 60092-353

Maximum conductor temperature : 90°C

<p><b>1- Ame</b> Cuivre étamé souple IEC 60228 Classe 5</p> <p><b>2- Isolation</b> Thermoplastique sans halogène type SHF2 - IEC 60092-359 Epaisseur suivant IEC 60092-353-1</p> <p>couleurs : noir – vert/jaune – rouge (autres couleurs sur demande)</p>		<p><b>1- Conductor</b> Flexible tinned copper IEC 60228 Class.5</p> <p><b>2- Insulation</b> Halogen-free thermoset compound in accordance with type SHF2 MUD resistant - IEC 60092-359 Thickness in accordance with IEC 60092-353-1</p> <p>colours : black – green/yellow – red (others on request)</p>
--	---	---



• **Approbation 'Marine':**  
- American Bureau of Shipping (ABS)







• **'Marine' Approval :**  
- American Bureau of Shipping (ABS)

• **Rayon de courbure** ⇨ 4 x Ø<sub>EXT.</sub>

• **Bending radius** ⇨ 4 x Ø<sub>OUT.</sub>

Température mini d'installation : -20°C

Minimum installation temperature : -20°C

 -40°C ; +90°C	 Flexible	 Bon Good	<p>FIRE RETARDANT</p>  IEC 60332-3-22 EN 50266-2-2	<p>LOW SMOKE FUME ZERO HALOGENE</p>  IEC 61034-2 IEC 60754-1	
--	---	--	---	---	---

Section mm <sup>2</sup>	Diamètre approx. Approx. diameter mm	Poids de cuivre Copper Index (kg/km)	Masse Weight (kg/km)
<b>250 V</b>			
0.75	2,6	7,2	15
1.0	3,0	9,6	24
<b>1000 V</b>			
1.5	3,1	14,4	28
2.5	3,4	24	36
4	3,9	38	53

Section mm <sup>2</sup>	Diamètre approx. Approx. diameter mm	Poids de cuivre Copper Index (kg/km)	Masse Weight (kg/km)
6	4,4	58	72
10	5,6	96	120
16	6,7	154	190
25	8,3	240	307
35	9,6	336	380
50	11,3	480	520
70	13,2	672	720



CABLES INDUSTRIELS DE CHAMPAGNE – z.a.m. Les Crayères – F- 51520 LA VEUVE  
Tél. +33 (0)3 26 68 48 22 – Fax. +33 (0)3 26 68 59 64 – [www.cic-cables.com](http://www.cic-cables.com)